



Power-Foam Bravo Heavy Duty Stripper for Spot Buildups

Version Number: 1

Preparation date: 2014-05-12

1. IDENTIFICATION

Product name: Power-Foam Bravo Heavy Duty Stripper for Spot Buildups
Product Code: 94966769
SDS #: MS0800173
Recommended use:

- Industrial/Institutional
- Floor care

Uses advised against: Uses other than those identified are not recommended

Manufacturer, importer, supplier:
 US Headquarters
 Diversey, Inc.
 8310 16th St.
 Sturtevant, Wisconsin 53177-1964
 Phone: 1-888-352-2249
 MSDS Internet Address: www.diversey.com

Canadian Headquarters
 Diversey, Inc. - Canada
 2401 Bristol Circle
 Oakville, Ontario L6H 6P1
 Phone: 1-800-668-3131

Emergency telephone number: 1-800-851-7145 (U.S.); 1-651-917-6133 (Int'l)

2. HAZARDS IDENTIFICATION

Classification for the undiluted product

Skin corrosion/irritation Category 1B
 Serious eye damage/eye irritation Category 1
 Flammability Extremely flammable aerosol, Category 1

**Signal Word:****Danger**

Precautionary Statements

EXTREMELY FLAMMABLE AEROSOL. HEATING MAY CAUSE AN EXPLOSION. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. CAUSES SEVERE SKIN BURNS AND SERIOUS EYE DAMAGE.

Avoid contact with eyes, skin and clothing. Causes burns/ serious damage to mouth, throat and stomach. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Keep container tightly closed. Do not pierce or burn, even after use. Do not incinerate. Do not breathe spray. Wash affected areas thoroughly after handling. Wear chemical-splash goggles, chemical-resistant gloves and protective footwear. IF SWALLOWED: Rinse mouth. DO NOT induce vomiting unless directed to do so by medical personnel. Drink a cupful of milk or water. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water for at least 15 minutes. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing for at least 15 minutes. Immediately call a Poison Center (1-800-851-7145) or doctor/physician. Wash contaminated clothing before reuse. Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures exceeding 50°C (122°F) which may cause bursting. Dispose of in accordance with all federal, state and local applicable regulations.

Health hazards not otherwise classified (HHNOC) - Not applicable

Physical hazards not otherwise classified (PHNOC) - Not applicable

Classification for the diluted product @ @ RTU

This product is intended to be used neat.

Precautionary Statements

3. COMPOSITION/INFORMATION ON INGREDIENTS

Classified Ingredients

Ingredient(s)	CAS #	Weight %
Isobutane	75-28-5	5 - 10%
Potassium hydroxide	1310-58-3	3% - < 5%
Diethylene glycol butyl ether	112-34-5	3% - < 5%
Ethoxylated secondary alcohol	84133-50-6	1% - < 3%
2-butoxyethanol	111-76-2	1% - < 3%
Monoethanolamine	141-43-5	1% - < 3%
Benzyl alcohol	100-51-6	1% - < 3%

*Exact percentages are being withheld as trade secret information

4. FIRST AID MEASURES

Undiluted Product:

Eyes: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing for at least 15 minutes.

Skin: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water for at least 15 minutes.

Inhalation: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Ingestion: IF SWALLOWED: Rinse mouth. DO NOT induce vomiting unless directed to do so by medical personnel. Drink a cupful of milk or water.

Most Important Symptoms/Effects: No information available.

Immediate medical attention and special treatment needed Not applicable.

Aggravated Medical Conditions: Individuals with chronic respiratory disorders such as asthma, chronic bronchitis, emphysema, etc., may be more susceptible to irritating effects.

Diluted Product:

This product is intended to be used neat.

Eyes: See undiluted product information above.

Skin: See undiluted product information above.

Inhalation: See undiluted product information above.

Ingestion: See undiluted product information above.

5. FIRE-FIGHTING MEASURES

Specific methods:

Aerosol Product - Containers may rocket or explode in heat of fire Use water spray to keep fire-exposed containers cool

Suitable extinguishing media:

Use dry chemical, CO₂, water spray or "alcohol" foam.

Specific hazards:

Aerosol product - Containers may rocket or explode in heat of fire. NFPA 30B Level 1 Aerosol.

Special protective equipment for firefighters: As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Extinguishing media which must not be used for safety reasons: No information available.

6. ACCIDENTAL RELEASE MEASURES

**Personal precautions:
Environmental precautions
and clean-up methods:**

Put on appropriate personal protective equipment (see Section 8.).
Clean-up methods - large spillage. Remove all sources of ignition. Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal. Use a water rinse for final clean-up.

7. HANDLING AND STORAGE

Handling: Avoid contact with skin, eyes and clothing. Do not taste or swallow. Avoid breathing vapors or mists. Use only with adequate ventilation. Remove and wash contaminated clothing and footwear before re-use. Wash thoroughly after handling. Product residue may remain on/in empty containers. All precautions for handling the product must be used in handling the empty container and residue. Do not let product overspray on to the floor as the product's ingredients could make the floor slippery. FOR COMMERCIAL AND INDUSTRIAL USE ONLY.

Storage:

NFPA 30B Level 1 Aerosol. Protect from freezing. Store in a cool, dry, well ventilated area away from heat or open flame. Do not pierce or burn, even after use. KEEP OUT OF REACH OF CHILDREN.

Aerosol Level (if applicable) : Not applicable

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines:

Ingredient(s)	CAS #	ACGIH	OSHA
Isobutane	75-28-5	1000 ppm (STEL)	-
Potassium hydroxide	1310-58-3	2 mg/m ³ (Ceiling)	-
Diethylene glycol butyl ether	112-34-5	10 ppm (TWA)	-
Ethoxylated secondary alcohol	84133-50-6	-	-
2-butoxyethanol	111-76-2	20 ppm (TWA)	Skin 50 ppm (TWA) 240 mg/m ³ (TWA)
Monoethanolamine	141-43-5	6 ppm (STEL) 3 ppm (TWA)	3 ppm (TWA) 6 mg/m ³ (TWA)
Benzyl alcohol	100-51-6	-	-

Undiluted Product:

Engineering measures to reduce exposure:

Good general ventilation should be sufficient to control airborne levels Respiratory protection is not required if good ventilation is maintained.

Personal Protective Equipment

Eye protection: Chemical-splash goggles.
Hand protection: Chemical-resistant gloves.
Skin and body protection: Protective footwear. If major exposure is possible, wear suitable protective clothing and footwear.
Respiratory protection: In case of insufficient ventilation wear suitable respiratory equipment. A respiratory protection program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.
Hygiene measures: Handle in accordance with good industrial hygiene and safety practice.

Diluted Product:

This product is intended to be used neat.

Personal Protective Equipment

Eye protection: Chemical-splash goggles.
Hand protection: Chemical-resistant gloves.
Skin and body protection: Protective footwear. If major exposure is possible, wear suitable protective clothing and footwear.
Respiratory protection: In case of insufficient ventilation wear suitable respiratory equipment. A respiratory protection program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.
Hygiene measures: Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES:

Physical State: Pressurized Liquid
Evaporation Rate: No information available
Odor threshold: No information available.
Melting point/range: Not determined
Autoignition temperature: No information available
Solubility in other solvents: No information available
Density: 8.26 lbs/gal 0.99 Kg/L
Bulk density: No information available
Flash point: 19 °F -7.0 °C
Dilution Flash Point: 19 °F -7.0 °C
Elemental Phosphorus: 0.06 % by wt.
pH: 13.0
Dilution pH: 13.0 @ RTU
Metal Corrosion Not determined
Flame Extension (inches): 0
Explosion limits: - upper: Not determined - lower: Not determined

Color: Clear, White
Odor: Solvent
Boiling point/range: Not determined
Decomposition temperature: Not determined
Solubility: Completely Soluble
Relative Density (relative to water): 0.99
Vapor density: No information available
Vapor pressure: No information available.
Partition coefficient (n-octanol/water): No information available
Viscosity: No information available
VOC: 10.72 % *
VOC % by wt. at use dilution 10.72 % *
Flammability (Solid or Gas): Not applicable

* - Title 17, California Code of Regulations, Division 3, Chapter 1, Subchapter 8.5, Article 2, Consumer Products, Sections 94508

10. STABILITY AND REACTIVITY

Reactivity: Not Applicable
Stability: The product is stable
Hazardous decomposition products: None known.
Materials to avoid: Acids.
Conditions to avoid: Keep away from heat. Keep away from open flames, hot surfaces and sources of ignition.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure:
Eye contact, Skin contact, Inhalation, Ingestion

Delayed, immediate, or chronic effects and symptoms from short and long-term exposure

Skin contact: Corrosive. Causes severe burns. Symptoms may include burns, blisters, redness and pain (which may be delayed).

Eye contact: Corrosive. Causes serious eye damage. Symptoms may include pain, burning sensation, redness, watering, blurred vision or loss of vision.

Ingestion: Causes burns/ serious damage to mouth, throat and stomach. Symptoms may include stomach pain and nausea.

Inhalation: May cause irritation and corrosive effects to nose, throat and respiratory tract. Symptoms may include coughing and difficulty breathing.

Sensitization: No known effects.

Numerical measures of toxicity

ATE - Oral (mg/kg): >5000

ATE - Dermal (mg/kg): >5000

ATE - Inhalatory, mists (mg/l): >20

ATE - Inhalatory, vapors (mg/l): >50

12. ECOLOGICAL INFORMATION

Ecotoxicity: No information available.

Persistence and Degradability: No information available.

Bioaccumulation: No information available.

13. DISPOSAL CONSIDERATIONS

Waste from residues / unused products: This product, as sold, if discarded or disposed, is a hazardous waste according to Federal regulations (40 CFR 261.4 (b)(4)). Dispose in compliance with all Federal, state, provincial, and local laws and regulations. Use up contents if possible before disposal. If possible, recycle empty aerosol cans to the nearest steel recycling center.

Contaminated Packaging: Do not re-use empty containers.

RCRA Hazard Class (undiluted product): D001 Ignitable Waste D002 Corrosive Waste

14. TRANSPORT INFORMATION

DOT/TDG/IMDG: Please refer to the Diversey HazMat Library, only available through Internet Explorer, <http://naextranet.diversey.com/dot/>, for up to date shipping information.

DOT (Ground) Bill of Lading Description: LTD. QTY.

IMDG (Ocean) Bill of Lading Description: UN1950, AEROSOLS, 2.1, LTD. QTY.

15. REGULATORY INFORMATION

International Inventories at CAS# Level

All components of this product are listed on the following inventories: U.S.A. (TSCA), Canada (DSL/NDSL).

U.S. Regulations

California Proposition 65: This product is not subject to the reporting requirements under California's Proposition 65.

RIGHT TO KNOW (RTK)

Ingredient(s)	CAS #	MARTK:	NJRTK:	PARTK:	RIRTK:
Water	7732-18-5	-	-	-	-
Isobutane	75-28-5	X	X	X	-
Potassium hydroxide	1310-58-3	X	X	X	X
Diethylene glycol butyl ether	112-34-5	-	X	-	-
Ethoxylated secondary alcohol	84133-50-6	-	-	-	-
2-butoxyethanol	111-76-2	X	X	X	-
Monoethanolamine	141-43-5	X	X	X	-
Benzyl alcohol	100-51-6	X	-	X	-

CERCLA/ SARA

Ingredient(s)	CAS #	Weight %	CERCLA/SARA RQ (lbs)	Section 302 TPQ (lbs)	Section 313
Potassium hydroxide	1310-58-3	3.96	1000		
Diethylene glycol butyl ether	112-34-5	3.04			X
2-butoxyethanol	111-76-2	1.96			X

Ingredient(s)	CAA HAP	CAA ODS	CWA Priority Pollutants
Diethylene glycol butyl ether	X		
2-butoxyethanol	X		

SARA 311/312 Hazard Categories

Immediate: X
Delayed: -
Fire: X
Reactivity: -
Sudden Release of Pressure: X

Canada

Ingredient(s)	CAS #	NPRI
Diethylene glycol butyl ether	112-34-5	X
2-butoxyethanol	111-76-2	X

16. OTHER INFORMATION

NFPA

Health 3

Flammability 4

Instability 0

Version Number: 1

Preparation date: 2014-05-12

Reason for revision: Not applicable

Prepared by: NAPRAC

Additional advice:

- Does not contain an added fragrance

Notice to Reader: This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained within. Actual conditions of use and handling are beyond seller's control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State, Provincial and Local laws and regulations.